

SAD
3
4-22-02
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF
SERIAL No.
FOR
FILED
ATTORNEY DOCKET NO.

ALLEN

~~Unknown~~

A BRUSH

~~Herewith~~

WPT 2-0030

Cleveland, Ohio 44114-2518
March 6, 2002

10/092322
Jc996 U.S. PTO



TRANSMITTAL LETTER OF 35 U.S.C. § 119 FOREIGN PRIORITY CLAIM
FOREIGN PRIORITY DOCUMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Applicant hereby claims priority under 35 U.S.C. § 119 for the
above-identified U.S. patent application. This claim of priority is based upon
British Application No. GB-0106334.6, filed March 15, 2001. A certified copy
of this prior British application is enclosed.

Respectfully submitted,

FAY, SHARPE, FAGAN,
MINNICH & McKEE, LLP

Steven M. Haas
Reg. No. 37,841
1100 Superior Avenue, Seventh Floor
Cleveland, Ohio 44114-2518
Telephone (216)861-5582
Facsimile (216)241-1666

Express Mail Certificate

I hereby certify that this TRANSMITTAL LETTER and ASSIGNMENT are being deposited with
the United States Postal Service by EXPRESS MAIL in an envelope numbered EV 020234115 US
addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231 on
March 6, 2002.

Steven M. Haas



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c.,
~~plc, P.L.C. or PLC.~~

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated


28 January 2002

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

AW/P200621GB

2. Patent application number
(The Patent Office will fill in this part)

0106334.6**15 MAR 2001**

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Anthony ALLENY Five Mile Caravan Site,
Kingswells, ABERDEEN, Scotland, AB15 8PDD

Patents ADP number (if you know it) **77300 88001**

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

A BRUSH

5. Name of your agent (if you have one)

W. P. Thompson & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Kings Building
South Church Side
HULL
East Yorkshire
HU1 1RR

Patents ADP number (if you know it)

0000158004 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

No

- a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	-
Description	5
Claim(s)	-
Abstract	-
Drawing(s)	1

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	--
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11. I/We request the grant of a patent on the basis of this application.

Signature W. P. Thompson & Co. Date 14/3/2001

W. P. THOMPSON & CO.

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. A. J. A. Walker
Tel: 01482 223451

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

DESCRIPTION"A BRUSH"

5 The present invention relates to a brush and more specifically to a brush for use
in a cleaning tool for removing debris from the interior wall of a pipeline or well casing
alone or in combination with solvents.

Due to operating and environmental conditions, oil, gas and water well casings
and pipes require regular cleaning to remove debris and deposits which build up over
time. A wide variety of cleaning tools for this purpose are known, including several
10 which rely on bristles disposed in and around the outer surface of the cleaning tool.

One such cleaning tool is disclosed in GB-2299599 and comprises a body
member having one or more cleaning pads each mounted in a respective recess in the
outer surface thereof and secured in place by a removable retaining device. Each of the
cleaning pads comprises a body which may be comprised of aluminium or polyurethane
15 fibre compound from an outer face of which bristles protrude. The bristles are mounted
to a backing material of fabric or soft rubber material which is bonded to the body.

Another such cleaning tool is disclosed in PCT/US93/08040 and comprises a
cylindrical metal sleeve which supports a jacket of foam like material. A swath of steel
bristles extends helical around the jacket. This helical swath comprises a fabric backing
20 strip into which the steel bristles are inserted. To minimise the likelihood of the bristles
coming loose from the fabric backing strip the bristles are formed from U-shaped
staples which are inserted through the rearward surface of the fabric backing strip.

In the wire brush industry, wire brushes are made by inserting steel bristles into pre-drilled holes in a brush body. These bristles are held in place by:

1. The push-fit of the bristle bundle in the pre-drilled hole, and/or
2. The outward pressure applied to the hole sides by a staple which is wrapped round the wire bundle as it is punched into the hole.

5

Where the brush body is comprised of a relatively soft material, such as plastics or wood, it allows the "spring" in the staple to make a slight indentation in the hole side, into which the staple relaxes. This gripping action by the staple then resists the removal of the bristle bundle. However, when the bristle bundle is punched into a metal brush body, the staple cannot open up and grip the hole in the same manner due to the hard, non-yielding nature of the metal body. This means that the bristle bundle is only held in by the friction at the bundle itself and the friction at the staple against the side of the hole.

10

It is an object of the present invention to provide a brush for use in a cleaning tool of the general type described hereinbefore which provides improved bristle retention.

15

According to the present invention there is provided a brush comprising a first body and a second body mounted on the first body, the first body having a first set of holes therein and the second body having a second set of through holes therein corresponding in number and spacing to the first set of through holes, wherein the first body is moveable relative to the second body between a first position in which each hole in the first set is aligned with a respective hole in the second set to receive

20

therethrough a bristle bundle, and a second position in which each pair of holes is misaligned to clamp the bristle bundle, and means for retaining the first body in the second position.

5 In a preferred embodiment of the present invention the first body comprises a cylinder and the second body comprises a cylindrical sleeve in which the first body is coaxially received. The inner cylinder may be moved longitudinally relative to the cylindrical sleeve between the first and second positions, or it may be rotated. The brush may comprise part of a cleaning tool or be adapted to be coupled to a cleaning tool. Alternatively, the brush may form a portion of a length of drill string.

10 In an alternative embodiment of the present invention the first and second bodies define a cleaning pad which is adapted in use to be mounted on a cleaning tool such as the one described in GB-2299599.

The bristles may be of nylon. Alternatively, the bristles may be of wire, such as flame hardened steel or copper. Preferably, a staple or ring is wrapped around the
15 inner end of each bristle bundle to further improve retention thereof between the first and second bodies.

The first and second bodies may be comprised of a resin fibre compound, for example, polyurethane fibre compound, or may be comprised of a malleable metal such as aluminium.

20 An embodiment of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 shows a detail of a brush in accordance with the present invention in

which the first and second bodies thereof are in the first position; and

Fig. 2 which shows the first and second bodies in the second position to grip and clamp a bristle bundle.

Referring to the drawings the brush comprises a first body 1 and a second body 2. The first and second bodies 1 and 2 may be essentially planar and form a brush pad, or they may comprise a cylinder and an outer cylindrical sleeve slidable on the cylinder. In the detail of the brush shown in the drawings only one bristle bundle receiving hole is shown, but of course in the complete brush there are several bristle bundle receiving holes, the number, spacing and pattern of which is selected in accordance with the intended application. Each bristle bundle receiving hole is comprised of a through hole 3 in the second body 2 and a blind hole 4 in the first body 1. A bristle bundle 5 is located through the through hole 3 and into the blind hole 4.

As shown in Fig. 1 the first and second bodies 1 and 2 are positioned such that the through hole 3 is aligned with the blind hole 4. In this position the bristle bundle 5 can be freely inserted and withdrawn. As shown in Fig. 2 the first body 1 has been displaced relative to the second body 2 to form a staggered hole configuration between the through hole 3 and the blind hole 4. This staggered hole configuration effects a clamping action on the bristle bundle 5 and thereby prevent its withdrawal. To further improve retention of the bristle bundle 5 between the first and second bodies 1 and 2, a staple or ring 6 is wrapped around the innermost end thereof.

Once the first and second bodies have been displaced by the requisite amount, a locking pin/bolt or some position fixing method is applied to ensure that the first and

second bodies remain in the displaced position.

.....

.....




FIG 1




FIG 2